afts on the Road



MOMOE'S STAR

An Easy, Quilt As You Go Design **Betty Davis** Fort Walton Beach FL

Make this lovely quilt by fashioning a number of quilted hexagons sewn together at the edges. It makes an excellent quilters project for home or the road, because each hexagon is prepared separately.

MATERIALS NEEDED:

Twin Quilt (uses approximately 350 hexagons) 5 yds solid colored backing 4 yds fleece

Double/Queen Quilt (uses approximately 490 hexagons) 8 yds solid colored backing 6 yds fleece

For all sizes:


.24


Template plastic, tracing paper or light weight cardboard Permanent fine point felt tip pen Dress seamer (optional) 6" squares of patterned scraps for center inserts Needle & thread to match backing Glue stick Pins

- 1. Using the template plastic, make 1 scalloped template (Template A) and 1 hexagon template (Template B) from the pattern layout on page 25. Mark quilting pattern on Template B with felt pen for reference.
- 2. For each hexagon, cut 1 piece of backing material from Template A adding a 1/4" seam allowance all the way around - or use the dress seamer to add the 8. Lay two of the quilted seam allowance when marking the fabric. (The dotted line on Template A indicates stitch placement rather than a fold line.)
- Next, cut 1 each (without a seam allowance) from the fleece and print using Template B.
- 3. Clip backing 1/4" between each scallop. Fold the
- 1/4" seam allowance to the wrong side of the backing

GMC Motorhome Marketplace

- and baste close to the folded edge. (See figure 1)
- 4. Using the glue stick, attach a fleece hexagon to the wrong of a printed hexagon.NOTE: Glue sticks are made with water soluable glue that will wash away the first time you launder the quilt.
- 5. Glue fleece/print hexagon to the center of a solid backing. Be sure to position fleeced side against the wrong side of backing. (See figure 2)
- 6. Fold scallops of backing over the print; pin in place. Slipstitch scallops though the fleece, being careful not to stitch through the backing. (See figure 3)
- 7. Following quilting reference on Template B, mark quilting lines and quilt the piece by stitching through all three layers. (See figure 3)
- hexagons with right sides together. Using a close whipstitch, sew or piece them together along one side. Join other hexagons along adjacent edges until the desired quilt size is reached. (See figure 4)





If you have a craft you especially like working with on the road, please, share it and possibly a little bit about yourself with us. We will consider it for publication.